

## Product information Nr. 64110000

## KAJO-Mehrzweckfett KL 2 K

KAJO-Multi-Purpose Grease KL 2 K is based on high quality basic oils with lithium soaps (Li-12-hydroxystearates) as thickening agents. These provide excellent work resistance stability. Furthermore, KAJO-Multi-Purpose Grease KL 2 K contains ingredients improving the rust and corrosion protection.

## Practical advantages:

**KAJO-Multi-Purpose Grease KL 2 K** is designed as a universally applicable grease. Our product has been tried and tested in many cases. It is used as a friction and roller bearing grease on lubricating points of motor vehicles, lorries, industrial machinery, conveyors, building machines etc.

## Typical characteristics:

Properties	Value	Unit	Standard
Colour	natural tint		
Thickener	Li-12 Hydroxystearat		
NLGI Class	2		DIN 51 818
Worked penetration	265-295	0,1 mm	ASTM D 217
Penetration after extended working: 100.000 double strokes	< 20	0,1 mm	ASTM D 217
Dropping point	>180	°C	IP 396
Behaviour towards water 3 h / +90 °C	1		DIN 51 807-1
Emcor test Corrosion degree	0/1	evaluation grade	DIN 51 802
Copper corrosion 100 °C / 24 h	1A		DIN 51 811
Oil separation at 40 °C: 18 h: 7 d:	0,45 1,60	% %	DIN 51 817
Work temperature short-term	-30 up to +120 up to +130	°C °C	DIN 51 825
Marking	K 2 k-30		DIN 51 502

Version 4 revised: 13.06.2016 DR/MJ/MP/AO

<sup>-</sup> All ratings are average values and are subject to production-related fluctuations –