



## Product information

Nr. 66130000

# KAJO-Gear Flow Grease GLP 0 F

**KAJO-Gear Flow Grease GLP 0 F** is a natrium saponified gear grease which proved to be outstandingly workstable and extremely adhesive with its extreme pressure additives.

### *Practical advantages:*

**KAJO-Gear Flow Grease GLP 0 F** offers large advantages when applied in open and closed gears due to its outstanding sealing properties and adhesiveness.

The soap structure ensures only slight leak losses even with inappropriately sealed gears. The high

pressure absorption and the excellent wear properties guarantee a long durability.

**KAJO-Gear Flow Grease GLP 0 F** has established itself in a variety of grease-lubricated gear installations. The choice of the NLGI class depends on the gear. A too solid NLGI class causes undesired warmings which lead to an efficiency loss in the gear.

**KAJO-Gear Flow Grease GLP 0 F** is especially suitable for gear motors, drum motors, small gears in household appliances, angle grinders and drills.

### *Typical characteristics*

Property	Value	Unit	Standard
Colour	Natural coloured		
NLGI class	0		DIN 51 818
Worked penetration PW 60	355 -385	1/10 mm	DIN ISO 2137
Worked penetration difference after 100.000 strokes	< 20	1/10 mm	DIN ISO 2137
Dropping point	> 140	°C	IP 396
VKA O.K. load welding load	2400 2600	N	DIN 51 350-4
Operating temperature range	-20 up to +100	°C	DIN 51 825
Marking	GP 0 H-20		DIN 51 502

Version 3 revised: 03.06.2016 DR/MJ/Pos/AO

- All ratings are average values and are subject to production-related variations -

D-59609 Anröchte • Boschstr. 13 • Phone: ++49 (0)2947 881-0 • FAX: ++49 (0)2947 881-120 •  
email: [Schmierstoffe@KAJO.de](mailto:Schmierstoffe@KAJO.de) • Internet: [www.KAJO.de](http://www.KAJO.de)