

# SRS Magnum 4T



## 4-Stroke Motorcycle Engine Oil

February 2019

### Characteristics

**SRS Magnum 4T** is an engine oil specially developed for use in four-stroke motorcycle engines. It satisfies the technical demands of all motorcycle manufacturers, and is suitable for all air-cooled and water-cooled 4-stroke motorcycle engines. High engine cleanliness and wear protection increase the life of the engine. It is suitable for wet clutches. Grabbing and slipping clutches after a cold start are prevented.

### Application

**SRS Magnum 4T** is a mineral oil based high performance engine oil in the SAE 20W-50 viscosity range. Very good high temperature stability and high wear protection guarantee optimal lubrication even under unfavourable conditions. The engine is protected from deposits and oil-sludge, oil consumption is reduced significantly.

### Specifications

- SAE Grade 20W-50
- API SG
- JASO MA2

SRS Magnum 4T is product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Magnum 4T
SAE Grade		SAE J 300	20W-50
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0.888
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	DIN EN ISO 3104	150
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	DIN EN ISO 3104	16.7
Viscosity Index (VI)		DIN ISO 2909	119
Flash Point COC		DIN ISO 2592	235
Pour Point		DIN ISO 3016	-30

The above values may vary within the commercial limits.

**Made in Germany**